



VIVID

Streamline VIVID batten provides optimum lighting performance through a formed prismatic acrylic lens.

A popular choice for storerooms, corridors, workshops and general lighting, the VIVID is available in both a narrow or wide body.


Powder-coated in high gloss white and finished with quality end-caps, VIVID is wired complete with electronic (A2) ballast and T5 colour 840 triphosphor lamps.



Technical information

Polar Distribution Curve

Product Code	Wattage	Mounting	Body Option	Nominal Dim. (mm)		
				L	W	D
VV-N-114	1x14w T5	Surface	Narrow	570	70	110
VV-N-214	2x14w T5	Surface	Narrow	570	70	110
VV-N-124	1x24w T5	Surface	Narrow	570	70	110
VV-N-224	2x24w T5	Surface	Narrow	570	70	110
VV-N-128	1x28w T5	Surface	Narrow	1170	70	110
VV-N-228	2x28w T5	Surface	Narrow	1170	70	110
VV-N-135	1x35w T5	Surface	Narrow	1470	70	110
VV-N-235	2x35w T5	Surface	Narrow	1470	70	110
VV-N-154	1x54w T5	Surface	Narrow	1170	70	110
VV-N-254	2x54w T5	Surface	Narrow	1170	70	110
VV-W-114	1x14w T5	Surface	Wide	570	120	110
VV-W-214	2x14w T5	Surface	Wide	570	120	110
VV-W-124	1x24w T5	Surface	Wide	570	120	110
VV-W-224	2x24w T5	Surface	Wide	570	120	110
VV-W-128	1x28w T5	Surface	Wide	1170	120	110
VV-W-228	2x28w T5	Surface	Wide	1170	120	110
VV-W-135	1x35w T5	Surface	Wide	1470	120	110
VV-W-235	2x35w T5	Surface	Wide	1470	120	110
VV-W-154	1x54w T5	Surface	Wide	1170	120	110
VV-W-254	2x54w T5	Surface	Wide	1170	120	110



VV-W-228

Wiring Options

Code

DSI digital dimming ballast	-D1
DALI Eco digital dimming ballast	-D2
DALI Excel digital dimming ballast	-D3
1-10V Analogue dimming ballast	-D4
Emergency Single Point pack	-EM
Fused terminal block	-FTB
T5 Colour 830 Triphosphor Lamp	-3K