



ARIS

ARIS utilises an extruded prismatic wrap around lens incorporating sonically welded prismatic end-caps for efficient and even light distribution.

Low in height with the flexibility to position end to end mounting, the ARIS is a stylish and functional luminaire.


Powder-coated to a high gloss white finish, ARIS is available in both narrow and wide body, and is wired complete with electronic (A2) ballast and T5 colour 840 triphosphor lamps.



Technical information

Polar Distribution Curve

Product Code	Wattage	Mounting	Body Option	Nominal Dim. (mm)		
				L	W	D
AR-N-114	1x14w T5	Surface	Narrow	640	190	95
AR-N-214	2x14w T5	Surface	Narrow	640	190	95
AR-N-124	1x24w T5	Surface	Narrow	640	190	95
AR-N-224	2x24w T5	Surface	Narrow	640	190	95
AR-N-128	1x28w T5	Surface	Narrow	1250	190	95
AR-N-228	2x28w T5	Surface	Narrow	1250	190	95
AR-N-135	1x35w T5	Surface	Narrow	1550	190	95
AR-N-235	2x35w T5	Surface	Narrow	1550	190	95
AR-N-154	1x54w T5	Surface	Narrow	1250	190	95
AR-N-254	2x54w T5	Surface	Narrow	1250	190	95
AR-W-114	1x14w T5	Surface	Wide	640	305	95
AR-W-214	2x14w T5	Surface	Wide	640	305	95
AR-W-124	1x24w T5	Surface	Wide	640	305	95
AR-W-224	2x24w T5	Surface	Wide	640	305	95
AR-W-128	1x28w T5	Surface	Wide	1250	305	95
AR-W-228	2x28w T5	Surface	Wide	1250	305	95
AR-W-135	1x35w T5	Surface	Wide	1550	305	95
AR-W-235	2x35w T5	Surface	Wide	1550	305	95
AR-W-154	1x54w T5	Surface	Wide	1250	305	95
AR-W-254	2x54w T5	Surface	Wide	1250	305	95



AR-N-228

Wiring Options

Code

DSI digital dimming ballast	-D1
DALI Eco digital dimming ballast	-D2
DALI Excel digital dimming ballast	-D3
1-10V Analogue dimming ballast	-D4
Emergency Single Point pack	-EM
Fused terminal block	-FTB
Colour 830 Triphosphor Lamp	-3K