

QUICKFIT VANDAL LED



Australume QUICKFIT VANDAL is a robust IK10 classified easy to install LED luminaire suitable for car parks, sporting facilities, high traffic public areas and correctional centres. It features a durable white powder coated metal body and polycarbonate diffuser and ends for efficient light distribution and impact resistance.


Installation is quick and simple, with a patented design, the base is mounted and hard wired, then a slide on mechanism enables the gear tray to connect to the base via a male/female type plug arrangement. Installation and servicing times are drastically reduced. Luminaire is completely serviceable and futureproof. Options include custom lumen packages, Dimming control gear, Microwave Sensor and Emergency Lighting.

Technical information

Features

- High quality IK10 rated metal fitting with powder coated body with high transmission opal Polycarbonate diffuser and ends
- Allows for rapid installation with gear tray connection via keyed male and female plugs
- Efficiency 120LPW & lumen maintenance L90 / B10 > 60,000 hours
- MacAdam Step 3 tolerance with CRI > 80 standard, CRI90 optional
- Emergency pack options available, Classifications for 1200mm CO D80, C90 D63 and for 600mm CO D63, C90 D50
- Motion detector option for ON / OFF or Corridor function 10 – 100% Bi-light level operation
- Patent Design
- 5 year warranty T&C's apply

Polar Distribution Curve



QFV50002L

Product Code	Delivered Lumens	Wattage	Mounting	Nominal Dim.(mm)		
				L	W	D
QFV13001L	1300	10	Surface	665	120	90
QFV25001L	2500	20	Surface	665	120	90
QFV26002L	2600	20	Surface	1225	120	90
QFV31002L	3100	26	Surface	1225	120	90
QFV50002L	5000	41	Surface	1225	120	90
QFV62002L	6200	52	Surface	1225	120	90
QFV77002L	7700	61	Surface	1225	120	90
QFV39003L	3900	33	Surface	1525	120	90
QFV64003L	6400	51	Surface	1525	120	90

Applications

Car parks, stairwells, public areas, sporting facilities and correctional centres.

Wiring Options

Code	Temperature Options
Wireless Bluetooth Dimming Gear -BT	3000K
DALI, DSI and SwitchDim Dimming Gear -D	4000K
Emergency Single Point -EM	5000K
Emergency DALI -DEM	6500K
Microwave Sensor for on/off operation -MS	
Corridor Function (add to -MS option) -CF	

Code

Temperature Options

Code

Additional Options

Code

Black Body -B
Suspension Kit -SUS
Vandal Screws -VS

**Custom lumen packages available on request*